
Selection: Semi-hermetic Reciprocating Compressors

Input Values

Compressor model	4DES-7Y
Mode	Refrigeration and air conditioning
Refrigerant	R404A
Reference temperature	Dew point temp.
Evaporating SST	-10,00 °C
Condensing SDT	45,0 °C
Liq. subc. (in condenser)	0 K
Suct. gas superheat	10,00 K
Operating mode	Auto
Power supply	380V-3-60Hz
Capacity control	100%
Useful superheat	100%




Result

Compressor	4DES-7Y-20D
Capacity steps	100%
Cooling capacity	14,77 kW
Cooling capacity *	16,19 kW
Evaporator capacity	14,77 kW
Power input	7,21 kW
Current (380V)	13,11 A
Voltage range	360-400V
Condenser capacity	22,0 kW
COP/EER	2,05
COP/EER *	2,25
Mass flow	524 kg/h
Operating mode	Standard
Discharge gas temp. w/o cooling	73,2 °C

Tentative data. The values are based on tentative data. Larger deviations may occur at the limits of the application range or under special operating conditions. The values must be tested and validated in the respective system before any binding design decision or release.
*According to EN12900 (20°C suction gas temp., 0K liquid subcooling)

Application Limits 100% 4DES-7




Legend

- additional cooling or suction gas superheat ≤20K
- additional cooling or max. toh <0°C
- M1: motor 1
- M2: motor 2
- A

Technical Data: 4DES-7Y

Dimensions and Connections



Legend of connection positions according to "Dimensions":

1 High pressure connection (HP) Connection for high pressure switch (HP)
1a High pressure transmitter connection (HP)
1b Additional high pressure connection (HP)
2 Connection for discharge gas temperature sensor (HP)
3 Low pressure connection (LP) Connection for low pressure switch (LP)
3a Low pressure transmitter connection (LP)
4 Connection for RI/CIC injection nozzle (LP)
4b Connection for RI/CIC sensor
4c Connection for RI/CIC sensor (MP / operation with refrigerant subcooler)
5 Oil fill plug
6 Oil drain
7 Oil filter (magnetic screw)
8 Oil return (from oil separator)
8* Oil return for NH3 with insoluble oil
9 Connection for oil and gas equalization (parallel operation)
9a Connection for gas equalization (parallel operation)
9b Connection for oil equalization (parallel operation)
10 Connection for oil heater
11 Oil pressure connection +
12 Oil pressure connection –
13 Cooling water connection
14 Intermediate pressure connection (MP)
15 Refrigerant injection (operation without liquid subcooler and with thermostatic expansion valve)
16 Connection for oil monitoring (oil level or oil differential pressure)
17 Refrigerant inlet on the subcooler
18 Refrigerant outlet on the subcooler
19 Clamp space
20 Terminal plate
21 Maintenance connection for oil valve
22 Pressure relief valve to the atmosphere (discharge gas side)
23 Pressure relief valve to the atmosphere (suction side)
24 Module housing (IQ MODULE inside)
25 Actuator sensor unit of oil level controller
26 Sight glass
27 Terminal box
SL Suction gas line
DL Discharge gas line
Dimensions can show tolerances according to EN ISO 13920-B.

Technical Data

Technical Data	
Displacement (1450rpm 50Hz)	26,8 m3/h
Displacement (1750rpm 60Hz)	32,4 m3/h
No. of cylinder x bore x stroke	4 x 50 mm x 39,3 mm
Weight	100 kg
Max. pressure (LP/HP)	19 / 32bar
Connection suction line	28 mm - 1 1/8"
Connection discharge line	22 mm - 7/8"
Oil type R134a/R407C/R404A/R507A/R407A/R407F	BSE32(Standard) | R134a tc>70°C: BSE55 (Option)
Oil type R22 (R12/R502)	B5.2 (Option)
Oil type R1234yf	BSE32 (Standard) | R1234yf tc>70°C : BSE55 (Option)
Oil type R1234ze	BSE55 (Standard) | to>15°C: BSE85K (Option) | tc>70°C: BSE85K (Option)
Oil type R454C/R455A	BSE32 (Standard)
Motor data	
Motor version	1
Motor voltage (more on request)	360-400V Y-3-60Hz
Max. operating current	21.0 A
Starting current (Rotor locked)	104.6 A
Max. power input	10,7 kW
Extent of delivery (standard)	
Motor protection	SE-B3 (Option), SE-B2 (Option), CM-RC-02 (Standard)
Enclosure class	IP66
Vibration dampers	Standard
Oil charge	2,00 dm³
Discharge shut-off valve	Standard
Suction shut-off valve	Standard
Available options	
Discharge gas temperature sensor	Option
Start unloading	Option
Capacity control	100-50% (Option)
Capacity Control - infinite	100-10% (Option)
Additional fan	Option
Oil heater	0..120 W PTC (Option)
Oil level monitoring	OLC-K1 (Option)
Sound measurement	
Sound power level (+5°C / 50°C)	70,7 dB(A) @ 50Hz
Sound power level (-10°C / 45°C)	73,6dB(A) @ 50Hz
Sound power level (-35°C / 40°C)	74,5 dB(A) @ 50Hz
Sound pressure level @ 1m (+5°C / 50°C)	62,7 dB(A) @ 50Hz
Sound pressure level @ 1m (-10°C / 45°C)	65,66dB(A) @ 50Hz
Sound pressure level @ 1m (-35°C / 40°C)	66,5 dB(A) @ 50Hz

Semi-hermetic Reciprocating Compressors

Motor 1 = e.g. 4TES-12 with 12"HP", primary for air-conditioning (e.g. R22,R407C) and air-conditioning with R134a at high ambient temperatures.
Motor 2 = e.g. 4TES-9 with 8"HP", universal Motor for medium and low temperature application (e.g. R404A, R507A, R407A, R407F) and air-conditioning with R134a
Motor 3 = e.g. 4TES-8, for medium temperature applications and R134a

For more information concerning the application range use the "Limits" button.

Operation modes 4VES-7 to 6FE-44 and 44JE-30 to 66FE-88 with R407F/R407A/R22

CIC = liquid injection with low temperature application, suction gas cooled motor.

ASERCOM certified performance data

The Association of European Refrigeration Component Manufacturers has implemented a procedure of certifying performance data. The high standard of these certifications is assured by:

* plausibility tests of the data performed by experts.

* regular measurements at independent institutes.

These high efforts result in the fact that only a limited number of compressors can be submitted. Due to this not all BITZER compresors are certified until now. Performance data of compressors which fulfil the strict requirements may carry the label "ASERCOM certified". In this software you will find the label at the respective compressors on the right side below the field "result" or in the print out of the performance data. All certified compressors and further information are listed on the homepage of ASERCOM.

Condensing capacity

The condensing capacity can be calculated with or without heat rejection. This option can be set in the menu Program ☐ Options. The heat rejection is constantly 5 % of the power consumption. The condensing capacity is to be found in the line Condensing cap. (with HR) resp. Condensing capacity.

Data for sound emission

Data based on 50 HZ apllication (IP-units 60 Hz) and R404A if not declared.
Sound pressure level: values based on free field area conditions with hemisperhical sound emission in 1 meter distance.

General remarks regarding sound data

Listed sound data were measured under testing conditions in our laboratory. For this purpose the free-standing test sample is mounted on a solid foundation plate and the pipework is connected vibration-free to the largest extend possible. Suction and discharge lines are fixed in a flexible configuration, such that a transmission of vibrations to the environment can be largely excluded. In real installations considerable differences might be observed, compared to the measurements in the laboratory. The airborne sound emitted by the compressor can be reflected from surfaces of the system and this may increase the airborne sound level measured close to the compressor. Vibrations caused by the compressor are also transferred to the system by the compressor feet and piping depending on the damping ratio of the fixings. Thus, the vibrations can induce other components to such an extent that these components contribute to an increase in airborne sound emission. If required, the transfer of vibrations to the system can be minimized by suitable fixing and damping elements.